

CLAIM AMENDMENTS

1. (Currently Amended)

A digital camera comprising:

an image pickup device having an image capturing area for converting optical images of a photographic object into electrical signals to accumulate;

a readout controller to control readout of the electrical signals accumulated in the image capturing area of the image pickup device;

an image information acquiring section to acquire image information according to the electrical signals being readout under the control of the readout controller;

an image display controller for controlling a display section to display images based on the image information having been acquired by the image information acquiring section; and

a signal output process executing section for executing signal output processing to output electrical signals accumulated in a first output area within the image capturing area of the image pickup device at a first speed as well as to output electrical signals accumulated in ~~the~~ a second output area other than the first output area at a second speed higher than the first speed;

wherein the image information acquiring section acquires image information of a predetermined area according to electrical signals of the predetermined area within the first output area having been output by the signal output process executing section during the signal output processing, and

the image display controller controls to display a moving image based on the image information of the predetermined area acquired by the image information acquiring section in a first display area, corresponding to the predetermined area ~~within a display area of the image capturing area,~~ of the display section during the signal output processing, ~~as well as displaying~~ and to simultaneously display a predetermined still image in ~~the a~~ second display area other than the first display area ~~corresponding to the predetermined area in the display section.~~

2, (Original)

The digital camera of claim 1, wherein the predetermined still image is a predetermined color image.

3. (Currently Amended)

The digital camera of claim 1, wherein the image information acquiring section acquires whole display area image information corresponding to a whole display area of the display section based on the electrical signals being readout under the control of the readout controller at a starting timing of the signal output processing,

and the image display controller controls to display ~~an image,~~ as the predetermined still image on the second display section area during the signal output processing, based on image information in which the predetermined area image information having been acquired by the image information acquiring section is removed from the whole display area image information.

4. (Canceled)

5. (Currently Amended)

The digital camera of claim 1, further comprising an auto focus processing section for executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output process executing section executes the signal output

processing to output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed, and the image display controller controls to simultaneously display the moving image and the predetermined still image.

6. (Currently Amended)

The digital camera of claim 4 3, further comprising an auto focus processing section for executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output process executing section executes the signal output processing to output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed and the image display controller controls to simultaneously display the moving image and the predetermined still image.

7. (Currently Amended)

The digital camera of claim 1, further comprising an auto focus processing section for executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output process executing section executes the signal output processing to output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed and the image display controller controls to simultaneously display the moving image and the predetermined still image.— ,

wherein a predetermined area within the first output area includes a focus adjusting area where a focus adjusting position of the photographic object exists.

8. (Currently Amended)

The digital camera of claim 3, further comprising an auto focus processing section for executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the

auto focus processing is executed, the signal output process executing section executes the signal output processing to output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed and the image display controller controls to simultaneously display the moving image and the predetermined still image,

wherein a predetermined area within the first output area includes a focus adjusting area where a focus adjusting position of the photographic object exists.

9. (Canceled)

10. (Currently Amended)

The digital camera of claim 8, wherein the image information acquiring section acquires image information of the focus adjusting area based on the electrical signals of the focus adjusting area within the first output area having been output by the signal output process executing section during the auto focus processing, and

wherein the image display ~~information~~ controller controls to display ~~an~~ the predetermined still image based on image information in which the focus adjusting area image information having been acquired by the image information acquiring section is removed from the whole display area image information.

11. (Currently Amended)

A method for controlling a digital camera provided with an image pickup device having an image capturing area for converting optical images of a photographic object into electrical signals to accumulate and with a display section for displaying images based on image information, the method comprising:

reading out of the electrical signals accumulated in the image capturing area of the image pickup device;

acquiring image information according to the electrical signals;

displaying images based on the image information having been acquired; and

executing signal output processing to output electrical signals accumulated in a first output area within the image capturing area of the image pickup device at a first speed as well as to output electrical signals

accumulated in ~~the~~ a second output area other than the first output area at a second speed higher than the first speed;

acquiring image information of a predetermined area according to electrical signals of the predetermined area within the first output area during the signal output processing; and

displaying a moving image based on the image information of the predetermined area in a first display area, corresponding to the predetermined area ~~within a display area of the image capturing area,~~ of the display section during the signal output processing, ~~as well as~~ and simultaneously displaying a predetermined still image in ~~the~~ a second display area other than the first display area ~~corresponding to the predetermined area in the display section.~~

12. (Original)

The method of claim 11, wherein the predetermined still image is a predetermined color image.



13. (Currently Amended)

The method of claim 11, further comprising:

acquiring whole display area image information corresponding to a whole display area of the display section based on the electrical signals being readout at a starting timing of the signal output processing; and

displaying ~~an image as~~ the predetermined still image on the second display ~~section~~ area during the signal output processing, based on image information in which the predetermined area image information having been acquired is removed from the whole display area image information.

14. (Canceled)

15. (Currently Amended)

The digital camera of claim 11, further comprising a step of executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output processing is executed to output electrical signals accumulated in ~~a~~ the first output area within the image capturing area of the image pickup device at ~~a~~ the first speed as well as to output electrical signals accumulated in the second output area other than

the first output area at a the second speed higher than the first speed, and the moving image and the predetermined still image are simultaneously displayed.

16. (Currently Amended)

The digital camera of claim ~~14~~ 13, further comprising a step of executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output processing is executed to output electrical signals accumulated in a the first output area within the image capturing area of the image pickup device at a the first speed as well as to output electrical signals accumulated in the second output area other than the first output area at a the second speed higher than the first speed, and the moving image and the predetermined still image are simultaneously displayed.

17. (Currently Amended)

The method of claim 11, further comprising a step of executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output processing is executed to

output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed and the moving image and the predetermined still image are simultaneously displayed,

wherein a predetermined area within the first output area includes a focus adjusting area where a focus adjusting position of the photographic object exists.

18. (Currently Amended)

The method of claim 13, further comprising a step of executing an auto focus processing to adjust a focus automatically at the time of image capturing of a photographic object, wherein when the auto focus processing is executed, the signal output processing is executed to output the electrical signals accumulated in the first output area within the image capturing area of the image pickup device at the first speed as well as to output the electrical signals accumulated in the second output area other than the first output area at the second speed and the moving image and the predetermined still image are simultaneously displayed,

wherein a predetermined area within the first output area includes a focus adjusting area where a focus adjusting position of the photographic object exists.

19. (Canceled)

20. (Currently Amended)

The method of claim 18, further comprising:

acquiring image information of the focus adjusting area based on the electrical signals of the focus adjusting area within the first output area during the auto focus processing, and

displaying ~~an~~ the predetermined still image based on image information in which the focus adjusting area image information is removed from the whole display area image information.